



WARP PREPARATION
准备设备

ACCUTENSE TYPE C

ACCUTENSE rotational hysteresis yarn tensioner ACCUTENSE转动阻尼式纱线张力器

Your benefit

- Specially designed for fine glass filaments
- Easy handling
- Perfectly steady and smooth yarn tension controllable via power supply unit
- Yarn-friendly processing
- Yarn tension ranges between 2 cN and 35 cN
- Creel length compensation adjustable by segments
- Designed for high speeds

您的优势

- 专为较细的玻纤设计
- 易于操控
- 通过供电装置获得完美、平稳的纱线张力
- 柔和的纱线加工
- 纱线张力范围在2cN到35cN之间
- 纱架长度张力补偿可分段调整
- 适应高速



1 Yarn guide wheel
导纱轮

2 Optoelectronic yarn break detector
光电式纱线断头检测装置

Product features

产品特点

- Rotational hysteresis yarn tensioner
- Distinguishing feature: perfectly smooth running
- Specially designed for fine glass filaments
- 转动阻尼式纱线张力器
- 显著特征: 完全平稳的运行
- 适用于较细的玻纤

Options

选配

- Optoelectronic yarn break detector
- 光电式纱线断头检测装置

Technical facts

技术参数

Application 应用	for fine glass fibres 适用于较细的玻纤
Wheel 张力轮	special wheel made from aluminium and chromium-plated 铝质镀铬的特殊张力轮
Yarn tension range 纱线张力范围	2– 35 cN
Yarn count 纱线细度	yarn tension range from 2 tex to 10 tex 2tex到10tex
Speed 速度	up to 1,000 m/min 高达1000米/分
Pre-tensioner 预张力装置	disc pre-tensioner 张力盘式预张力装置
Eyelets 瓷眼	made from titanium dioxide 由二氧化钛制成