



WARP PREPARATION
准备设备

ACCUTENSE TYPE A AND B

ACCUTENSE rotational hysteresis yarn tensioner ACCUTENSE转动阻尼式纱线张力器

Your benefit

- Easy handling
- Perfectly steady and smooth yarn tension controllable via power supply unit
- Yarn-friendly processing
- Five different yarn tension ranges can be selected
- Creel length compensation adjustable by segments
- Designed for high speeds

您的优势

- 易于操控
- 通过供电装置获得完美、平稳的纱线张力
- 柔和的纱线加工
- 可以选择五种不同的纱线张力范围
- 纱架长度张力补偿可分段调整
- 适应高速



1 ACCUTENSE, Type B, 90° model
ACCUTENSE, B型, 90°模型

Product features

产品特点

- Rotational hysteresis yarn tensioner
- Distinguishing feature: perfectly smooth running
- 转动阻尼式纱线张力器
- 显著特征: 完全平稳的运行

Options

选配

- Three-piece Accu-Grip wheel
- Disc pre-tensioner
- Ceramic pin pre-tensioner
- Yarn break detector
- Optoelectronic yarn break detector
- 三片式Accu-Grip纱线摩擦轮
- 张力盘式预张力装置
- 瓷柱式预张力装置
- 纱线断头检测装置
- 光电式纱线断头检测装置

Technical facts

技术参数

| | |
|--------------------------------|---|
| Application 应用 | for monofil, multifil, glass fibre, carbon fibre, aramid fibre 适用于单丝、复丝、玻纤、碳纤维和芳纶纤维 |
| Two different types 两种不同的类型 | ACCUTENSE type A (30°) and ACCUTENSE type B (90°) AccuTense 型号 A (30°)和 AccuTense 型号 B (90°) |
| Yarn tension ranges 纱线张力范围 | 3–35 cN 5–60 cN 10–120 cN 50–200 cN 50–250 cN |
| Yarn count 纱线细度 | every yarn tension range from dtex 20 to dtex 2,200 每个张力范围都适应20dtex到2200dtex的纱线 |
| Speed 速度 | up to 1,000 m/min 高达1000米/分 |
| Pre-tensioner 预张力装置 | disc pre-tensioner or pin pre-tensioner 张力盘式预张力装置或者瓷柱式预张力装置 |
| Eyelets 瓷眼 | made from titanium dioxide or aluminium oxide 由二氧化钛或者氧化铝制成 |