



WARP KNITTING
经编机

OJ 83/1 B

LACE.EXPRESS Multibar Raschel machine for the production of elastic and inelastic lace all-overs and bands

智慧·花边多梳拉舍尔经编机, 生产高品质弹性和无弹满幅花边和条带的优质机型

Your benefit

- Maximize
 - Machine speed
 - Efficiency in operation
 - Fabric output
 - Flexibility by producing lace bands
- Minimize
 - Downtime for supporting activities
 - Energy consumption
- Enjoy
 - Usability of the machine
 - Quality of fabric
 - Turnover per machine

您的优势

- 最高的
 - 机器速度
 - 运行效率
 - 面料产量
 - 生产花边条带的灵活性
- 最少的
 - 因机器维护和设置产生的停机时间
 - 能源消耗
- 最佳的
 - 机器可用性
 - 织物品质
 - 每台机器带来的利润

OJ 83/1 B

Technical data

技术参数

	Stitch forming 成圈		Inlay lapping 衬纬											
	Ground bar 地梳		Pattern bars 花梳										Jacquard bars 贾卡梳	Ground bar 地梳
Shog line 横移线	1	2	3	4	5	6	7	8	9	10	11	12-13	14	
Patterning 花梳数		8	16	24	32	40	48	56	64	72	80			
Coarse yarn PB 11-26 粗纱 PB 11-26			LC-31	LC-31	LC-26	LC-26	LC-26	LC-26	LC-26	LC-26	LC-26			
Coarse yarn PB 11-42 粗纱 PB 11-42			LC-31	LC-31	LC-31	LC-31	LC-26	LC-26	LC-26	LC-26	LC-26			

Working width / Gauge

533 cm = 210 inches
E 18 / E 24

Yarn let-off device

Three electronically controlled yarn let-off gears for ground guide bars

Pattern device EL

Electronic guide bar control: ground guide bars and pattern guide bars (string bars)

KAMCOS®

(KARL MAYER COMMAND SYSTEM)

Operator interface to configure, control and adjust the electronic functionality of the machine

Fabric take-up

Electronically regulated fabric take-up, driven by geared motor, consisting of four rollers covered with black grip tape

Batching device

Batching device No. 51 free-standing, friction drive, max. batch diameter: 762 mm (30")

Electrical equipment

Speed-regulated drive, connected load 20 kVA

工作门幅/机号

533 cm = 210英寸
E 18 / E 24

送经机构

3套电子送经装置控制地梳

EL提花机构

电子横移系统控制地梳和花梳 (钢丝花梳)

卡迈酷斯® (卡尔迈耶控制系统)

操作界面, 用于设置、控制和调节机器的电控部分功能

织物牵拉机构

电子控制的织物牵拉, 通过电机传动, 由4个包覆黑色包布的罗拉组成

卷取机构

采用51号独立式卷取机构, 摩擦传动, 最大卷装直径762 mm (30英寸)

电子设备

调速传动, 机器总连接负载20 kVA

Total width 宽度
11450 mm
Total depth 纵深
6200 mm
Total height 高度
4600 mm

