

WARP KNITTING
经编机

MJ 52/1 S



LEISUREE.FASHION Multibar Jacquard Raschel machine for the production of high-quality elastic and patterned fabrics

LEISUREE.FASHION多梳拉舍尔经编机，生产高品质弹力花边面料的优质机型

Your benefit

- Maximise
 - machine speed
 - efficiency in operation
 - fabric output
- Minimise
 - downtime for supporting activities
- Enjoy
 - usability of the machine
 - turnover per machine











您的优势

- 最高的
 - 机器速度
 - 运行效率
 - 面料产量
- 最少的
 - 因机器维护和设置产生的停机时间
- 最佳的
 - 机器可用性
 - 每台机器带来的利润

MJ 52/1 S

Technical data

技术参数

	Stitch forming 成圈		Inlay lapping 衬纬							
	Jacquard bar 贾卡梳	Ground bar 地梳	Pattern bars 花梳				Ground bar 地梳			
										
Shogline 横移线	1-2	3	4	5	6	7	8	9	10	11
Patterning 花梳数			8	16	24	32	40	48		

Working width / Gauge

340 cm = 134 inches
E 28

Yarn let-off device

Five electronically controlled yarn let-off gears for ground guide bars and jacquard bars

Pattern device EL

Electronic guide bar control: ground guide bars, jacquard bars and pattern bars (string bars)

KAMCOS®

(KARL MAYER COMMAND SYSTEM)

Operator interface to configure, control and adjust the electronic functionality of the machine

Fabric take-up

Electronically regulated fabric take-up, driven by geared motor, consisting of four rollers covered with black grip tape

Batching device

Batching device No. 13D integrated, centrally driven, max. batch diameter: 762 mm (30")

Electrical equipment

Speed-regulated drive, connected load 25 kVA

工作门幅/机号

340 cm = 134英寸
E 28

送经机构

5套电子送经装置控制地梳和贾卡梳

EL提花机构

电子横移系统控制地梳、贾卡梳和花梳(钢丝花梳)

卡迈酷斯® (卡尔迈耶控制系统)

操作界面, 用于设置、控制和调节机器的电控部分功能

织物牵拉机构

电子控制的织物牵拉, 通过电机传动, 由4个包覆黑色包布的罗拉组成

卷取机构

采用13 D卷取机构, 轴心传动, 最大卷装直径: 762 mm (30英寸)

电子设备

调速传动, 机器总连接负载25 kVA

Total width 宽度

7700 mm

Total depth 纵深

6850 mm

Total height 高度

4500 mm

